

SID and Transition coding of RNAV RWY 35L**1. RNAV1 RWY 35L: HOKIN ONE ALPHA DEPARTURE (HOKIN 1A)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DN456	-	360°(359.2°)	0°40'W	30.6	-	-2450	-	RNAV1
2	TF	HOKIN	-	073°(072.5°)	0°40'W	43.2	-	-FL110	-	RNAV1

BINKU 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	HOKIN	-	-	0°40'W	-	-	-FL110	-	RNAV1
2	TF	BINKU	-	075°(074.0°)	0°40'W	43.8	-	-	-	RNAV1

2. RNAV1 RWY 35L: KEMSY ONE ALPHA DEPARTURE (KEMSY 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DN450	-	360°(359.2°)	0°40'W	13.0	-	+900	-	RNAV1
2	TF	DN451	-	090°(089.2°)	0°40'W	20.6	-	-	-465	RNAV1
3	TF	DN452	-	180°(179.3°)	0°40'W	9.3	-	-2450	-	RNAV1
4	TF	DN453	-	180°(179.3°)	0°40'W	20.3	-	+FL100	-	RNAV1
5	TF	KEMSY	-	180°(179.3°)	0°40'W	40.5	-	-	-	RNAV1

Note: Minimum PDG of 7% until reaching 900M.

KUMUN 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KEMSY	-	-	0°40'W	-	-	-	-	RNAV1
2	TF	KUMUN	-	146°(145.0°)	0°40'W	77.2	-	-	-	RNAV1

SADIN 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KEMSY	-	-	0°40'W	-	-	-	-	RNAV1
2	TF	SADIN	-	205°(204.6°)	0°40'W	56.4	-	-	-	RNAV1

XAQUA 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KEMSY	-	-	0°40'W	-	-	-	-	RNAV1
2	TF	SADIN	-	205°(204.6°)	0°40'W	56.4	-	-	-	RNAV1
3	TF	XAQUA	-	205°(204.6°)	0°40'W	19.5	-	-	-	RNAV1

3. RNAV1 RWY 35L: TANNA ONE CHARLIE DEPARTURE (TANNA 1C)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DN450	-	360°(359.2°)	0°40'W	13.0	-	+900	-	RNAV1
2	TF	DN451	-	090°(089.2°)	0°40'W	20.6	-	-	-	RNAV1
3	TF	DN452	-	180°(179.3°)	0°40'W	9.3	-	-2450	-	RNAV1
4	TF	DN453	-	180°(179.3°)	0°40'W	20.3	-	+FL100	-465	RNAV1
5	TF	DN454	-	270°(269.6°)	0°40'W	35.3	-	+FL180	-	RNAV1
6	TF	DN455	-	270°(269.5°)	0°40'W	14.0	-	-	-	RNAV1
7	TF	TANNA	-	270°(269.5°)	0°40'W	29.2	-	-	-	RNAV1

Note: Minimum PDG of 7% until reaching 900M.