

Procedure coding**1. RNP z RWY 07: APPROACH FROM VIBAO**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VIBAO	-	-	-	-	-1500 +1200	-	-	RNP APCH
2	TF	CI071	-	022 (020.2)	12.5	-	@750	-	-	RNP APCH
3	TF	CI070	-	074 (072.3)	7.4	-	@610	-	-	RNP APCH
4	TF	RWY07 (MAPT)	Y	074 (072.3)	11.3	-	@18	-	-3.00°/ 15.25	RNP APCH
5	CA	-	-	074 (072.3)	-	-	+300	-	-	RNP APCH
6	DF	VANUC	-	-	-	R	@900	-	-	RNP APCH
7	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNP APCH

2. RNP z RWY 07: APPROACH FROM CI072

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	CI072	-	-	-	-	+1200	-	-	RNP APCH
2	TF	CI071	-	074 (072.2)	13.0	-	@750	-	-	RNP APCH
3	TF	CI070	-	074 (072.3)	7.4	-	@610	-	-	RNP APCH
4	TF	RWY07 (MAPT)	Y	074 (072.3)	11.3	-	@18	-	-3.00°/ 15.25	RNP APCH
5	CA	-	-	074 (072.3)	-	-	+300	-	-	RNP APCH
6	DF	VANUC	-	-	-	R	@900	-	-	RNP APCH
7	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNP APCH

3. RNP z RWY 07: APPROACH FROM DAGSA

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	DAGSA	-	-	-	-	+1400	-	-	RNP APCH
2	TF	CI071	-	165 (163.0)	13.0	-	@750	-	-	RNP APCH
3	TF	CI070	-	074 (072.3)	7.4	-	@610	-	-	RNP APCH
4	TF	RWY07 (MAPT)	Y	074 (072.3)	11.3	-	@18	-	-3.00°/ 15.25	RNP APCH
5	CA	-	-	074 (072.3)	-	-	+300	-	-	RNP APCH
6	DF	VANUC	-	-	-	R	@900	-	-	RNP APCH
7	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNP APCH

4. RNP z RWY 07: APPROACH FROM DUMIM

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	DUMIM	-	-	-	-	+1200	-	-	RNP APCH
2	TF	CI071	-	345 (343.0)	13.0	-	@750	-	-	RNP APCH
3	TF	CI070	-	074 (072.3)	7.4	-	@610	-	-	RNP APCH
4	TF	RWY07 (MAPT)	Y	074 (072.3)	11.3	-	@18	-	-3.00°/ 15.25	RNP APCH
5	CA	-	-	074 (072.3)	-	-	+300	-	-	RNP APCH
6	DF	VANUC	-	-	-	R	@900	-	-	RNP APCH
7	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNP APCH

5. RNAV HOLDING:

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VIBAO	022 (020.2)	+1.5	1 ≤ FL140 1.5 > FL140	R	+1200	-430 ≤ FL140 -445 > FL140	RNP APCH
VANUC	307 (305.7)	+1.5	1 ≤ FL140 1.5 > FL140	R	+900	-430 ≤ FL140 -445 > FL140	RNP APCH