

## Procedure coding

### 1. RNP y RWY 07: APPROACH FROM VANUC

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VANUC	-	-	-	-	@900	-	-	RNP APCH
2	TF	DUMIM	-	307 (305.7)	18.9	-	-	-	-	RNP APCH
3	TF	CI071	-	345 (343.0)	13.0	-	@750	-	-	RNP APCH
4	TF	CI070	-	074 (072.3)	7.4	-	@610	-	-	RNP APCH
5	TF	RWY07 (MAPT)	Y	074 (072.3)	11.3	-	@18	-	-3.00°/15.25	RNP APCH
6	CA	-	-	074 (072.3)	-	-	+300	-	-	RNP APCH
7	DF	VANUC	-	-	-	R	@900	-	-	RNP APCH
8	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNP APCH

### 2. RNAV HOLDING:

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VANUC	307 (305.7)	+1.5	1 ≤ FL140 1.5 > FL140	R	+900	-430 ≤ FL140 -445 > FL140	RNP APCH