

Procedure coding

1. ILS wRWY07: INITIAL APPROACH SEGMENT FROM VANUC

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VANUC	-	-	-	-	@900	-	-	RNAV 1
2	TF	DUMIM	-	307 (305.7)	18.9	-	-	-	-	RNAV 1
3	TF	CI071	-	345 (343.0)	13.0	-	@750	-	-	RNAV 1

2. ILS wRWY07: MISSED APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	MAPT	Y	-	-	-	-	-	-	RNAV 1
2	CA	-	-	074 (072.3)	-	-	+300	-	-	RNAV 1
3	DF	VANUC	-	-	-	R	@900	-	-	RNAV 1
4	HM	VANUC	-	307 (305.7)	-	R	+900	-	-	RNAV 1

3. RNAV HOLDING:

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VANUC	307 (305.7)	+1.5	1 ≤ FL140 1.5 > FL140	R	+900	-430 ≤ FL140 -445 > FL140	RNAV 1