

Procedure coding

1. RNP yRWY 25: APPROACH FROM VANUC

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VANUC	-	-	-	-	@900	-	-	RNP APCH
2	TF	FILET	-	047 (045.0)	33.0	-	-	-	-	RNP APCH
3	TF	CI251	-	344 (342.4)	13.0	-	@750	-	-	RNP APCH
4	TF	CI250	-	254 (252.4)	7.4	-	@610	-	-	RNP APCH
5	TF	RWY25 (MAPT)	Y	254 (252.4)	11.3	-	@18	-	-3.00°/15.25	RNP APCH
6	CA	-	-	254 (252.3)	-	-	+300	-	-	RNP APCH
7	DF	VANUC	-	-	-	L	@900	-	-	RNP APCH
8	HM	VANUC	-	047 (045.0)	-	R	+900	-	-	RNP APCH

2. RNAV HOLDING:

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VANUC	047 (045.0)	+1.5	1 ≤ FL140 1.5 > FL140	R	+900	-430 ≤ FL140 -445 > FL140	RNP APCH