

Procedure coding

1. BATOT ONE CHARLIE ARRIVAL (BATOT 1C)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	BATOT	-	-	+1.5	-	-	-	-	RNAV 1
2	TF	HODOL	-	345 (343.0)	+1.5	20.4	-	+1850	-	RNAV 1
3	TF	BIGEL	-	345 (343.0)	+1.5	14.8	-	@1850	-	RNAV 1
4	TF	DUMIM	-	345 (343.0)	+1.5	14.8	-	-	-	RNAV 1
5	TF	CI073	-	255 (253.0)	+1.5	13.0	-	-	-	RNAV 1
6	TF	CI072	-	345 (343.0)	+1.5	12.8	-	+1200	-	RNAV 1

MAREL 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	MAREL	-	-	+1.5	-	-	-	-	RNAV 1
2	TF	BATOT	-	003 (001.1)	+1.5	109.5	-	-	-	RNAV 1

2. PHUTA ONE ECHO ARRIVAL (PHUTA 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	PHUTA	-	-	+1.5	-	-	@1850	-	RNAV 1
2	TF	DAGSA	-	147 (145.5)	+1.5	7.5	-	+1400	-	RNAV 1
3	TF	CI071	-	165 (163.0)	+1.5	13.0	-	-	-	RNAV 1
4	TF	DUMIM	-	165 (163.0)	+1.5	13.0	-	-	-	RNAV 1
5	TF	CI073	-	255 (253.0)	+1.5	13.0	-	-	-	RNAV 1
6	TF	CI072	-	345 (343.0)	+1.5	12.8	-	+1200	-	RNAV 1

3. RNAV HOLDING:

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PHUTA	Y	117 (115.0)	+1.5	1 ≤ FL140 1.5 > FL140	R	+1850	-430 ≤ FL140 -445 > FL140	RNAV 1
HODOL	Y	345 (343.0)	+1.5	1 ≤ FL140 1.5 > FL140	L	+1850	-430 ≤ FL140 -445 > FL140	RNAV 1