

Procedure coding**1. PHUTA ONE FOXTROT ARRIVAL (PHUTA 1F)**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1 | IF | PHUTA | - | - | +1.5 | - | - | - | - | RNAV 1 |
| 2 | TF | HALRO | - | 083 (081.9) | +1.5 | 23.5 | - | +2150 | - | RNAV 1 |
| 3 | TF | TOMUL | - | 084 (082.0) | +1.5 | 19.5 | - | +1200 | - | RNAV 1 |

2. VANUC ONE DELTA ARRIVAL (VANUC 1D)

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1 | IF | VANUC | - | - | +1.5 | - | - | - | - | RNAV 1 |
| 2 | TF | TOLUP | - | 020 (018.5) | +1.5 | 18.8 | - | +2150 | - | RNAV 1 |
| 3 | TF | FILET | - | 074 (072.3) | +1.5 | 18.3 | - | +1200 | - | RNAV 1 |

3. VIBAO ONE FOXTROT ARRIVAL (VIBAO 1F)

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1 | IF | VIBAO | - | - | +1.5 | - | - | - | - | RNAV 1 |
| 2 | TF | TOLUP | - | 080 (078.1) | +1.5 | 30.1 | - | +2150 | - | RNAV 1 |
| 3 | TF | FILET | - | 074 (072.3) | +1.5 | 18.3 | - | +1200 | - | RNAV 1 |

4. RNAV HOLDING:

| Holding Fix | Fly-over | Inbound Course/Track °M(°T) | Magnetic Variation | Time (min) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|-------------|----------|-----------------------------|--------------------|--------------------------|----------------|--------------|------------------------------|----------|
| PHUTA | Y | 117 (115.0) | +1.5 | 1 ≤ FL140 1.5 > FL140 | R | +1850 | -430 ≤ FL140 -445 > FL140 | RNAV 1 |
| FILET | Y | 344 (342.4) | +1.5 | 1 ≤ FL140 1.5 > FL140 | L | +1200 | -430 ≤ FL140 -445 > FL140 | RNAV 1 |