

Procedure coding**1. PHUTA ONE GOLF ARRIVAL (PHUTA 1G)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	PHUTA	-	-	+1.5	-	-	-	-	RNAV 1
2	TF	HALRO	-	083 (081.9)	+1.5	23.5	-	+2150	-	RNAV 1
3	TF	TOMUL	-	084 (082.0)	+1.5	19.5	-	-	-	RNAV 1
4	TF	CI251	-	164 (162.4)	+1.5	13.0	-	-	-	RNAV 1
5	TF	FILET	-	164 (162.4)	+1.5	13.0	-	-	-	RNAV 1
6	TF	CI253	-	074 (072.4)	+1.5	13.0	-	-	-	RNAV 1
7	TF	CI252	-	344 (342.4)	+1.5	13.0	-	+1200	-	RNAV 1

2. VANUC ONE ECHO ARRIVAL (VANUC 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VANUC	-	-	+1.5	-	-	-	-	RNAV 1
2	TF	TOLUP	-	020 (018.5)	+1.5	18.8	-	+2150	-	RNAV 1
3	TF	FILET	-	074 (072.3)	+1.5	18.3	-	-	-	RNAV 1
4	TF	CI253	-	074 (072.4)	+1.5	13.0	-	-	-	RNAV 1
5	TF	CI252	-	344 (342.4)	+1.5	13.0	-	+1200	-	RNAV 1

3. VIBAO ONE HOTELARRIVAL (VIBAO 1H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VIBAO	-	-	+1.5	-	-	-	-	RNAV 1
2	TF	TOLUP	-	080 (078.1)	+1.5	30.1	-	+2150	-	RNAV 1
3	TF	FILET	-	074 (072.3)	+1.5	18.3	-	-	-	RNAV 1
4	TF	CI253	-	074 (072.4)	+1.5	13.0	-	-	-	RNAV 1
5	TF	CI252	-	344 (342.4)	+1.5	13.0	-	+1200	-	RNAV 1

4. RNAV HOLDING:

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PHUTA	Y	117 (115.0)	+1.5	1 ≤ FL140 1.5 > FL140	R	+1850	-430 ≤ FL140 -445 > FL140	RNAV 1