



CHANGES: VAR, MAG BRG, UPDT AND ADDN OF RESTRICTED AREAS.
ATS ROUTES INFO, ADJUSTMENT AND ADDN OF

LEGEND	
CONTROL AREA	(TMA)
CONTROL ZONE	(CTR)
REPORTING POINT	(COMPULSORY) (ON REQUEST) (COMPULSORY/FLY-BY)
DEPARTURE/ARRIVAL ROUTING	
TRANSITIONAL ROUTE	
DISTANCE IN KILOMETRES	
LOWER LIMIT	2200 m
MAGNETIC BEARING	090°
RADIO NAVIGATION AID	NOI BAI DVOR/DME 116.1 NOB 21°12'47"N 105°50'06"E
AREA MINIMUM ALTITUDE (AMA)	
EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600 METRES IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL.	
EXAMPLE: 2300 METRES	230