

Procedure coding (cont.)**5. RNAV RWY 29L: JULUN ONE CHARLIE DEPARTURE (JULUN 1C)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(287.1)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	JULUN	-	349(347.2)	+2.0	51.2	-	+FL160	-	-	RNAV 1

DILEN 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	JULUN	-	-	+2.0	-	-	+FL160	-	-	RNAV 1
2	TF	DILEN	-	012(010.3)	+2.0	39.9	-	-	-	-	RNAV 1

6. RNAV RWY 29R: DIHAI ONE BRAVO DEPARTURE (DIHAI 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(286.7)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	NB291	-	019(017.1)	+2.0	16.7	-	+2450	-	-	RNAV 1
3	TF	NUCOC	-	062(060.2)	+2.0	24.1	-	+FL130	-	-	RNAV 1
4	TF	DIHAI	-	053(051.4)	+2.0	49.0	-	+FL150	-	-	RNAV 1

DENMO 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	DIHAI	-	-	+2.0	-	-	+FL150	-	-	RNAV 1
2	TF	DENMO	-	054(051.6)	+2.0	37.5	-	-	-	-	RNAV 1

NAKHA 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	DIHAI	-	-	+2.0	-	-	+FL150	-	-	RNAV 1
2	TF	NAKHA	-	070(068.2)	+2.0	40.4	-	-	-	-	RNAV 1

7. RNAV RWY 29R: FINAM ONE BRAVO DEPARTURE (FINAM 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(286.7)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	NB292	-	199(197.1)	+2.0	16.7	-	+2450	-	-	RNAV 1
3	TF	NB293	-	132(130.2)	+2.0	10.6	-	+FL100	-	-	RNAV 1
4	TF	SONTA	-	132(130.2)	+2.0	13.0	-	-	-	-	RNAV 1
5	TF	FINAM	-	146(144.4)	+2.0	64.0	-	+FL160	-	-	RNAV 1

NAH 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	FINAM	-	-	+2.0	-	-	+FL160	-	-	RNAV 1
2	TF	NAH	-	147(144.5)	+2.0	22.4	-	-	-	-	RNAV 1

8. RNAV RWY 29R: XUNBI ONE BRAVO DEPARTURE (XUNBI 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(286.7)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	XUNBI	-	240(237.9)	+2.0	46.9	-	-FL130	-	-	RNAV 1

MC 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	XUNBI	-	-	+2.0	-	-	-FL130	-	-	RNAV 1
2	TF	MC	-	240(238.0)	+2.0	52.4	-	-	-	-	RNAV 1