

APCH procedure coding of RNP X RWY 10

1. RNP X APCH RWY 10 FROM PQ501

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	GRADIENT	NAV PER
IF	PQ501	-	-	-	-	900	-	-	RNP APCH
TF	PQ510	-	53.7	317 (316.9)	-	-	-	-	RNP APCH
TF	PQ310	-	13.0	276 (275.7)	L	-	-	-	RNP APCH
TF	PQ110	-	13.0	186 (185.7)	L	800	-	-	RNP APCH
TF	PQ010	-	7.4	096 (095.7)	L	610	-	-	RNP APCH
TF	MIHER	Y	7.5	096 (095.7)	-	220	-	-5.2%	RNP APCH
DF	PQ500	Y	-	-	-	-	-	-	RNP APCH
TF	PQ501	-	33.5	138 (137.6)	R	900	-	-	RNP APCH
HM	PQ501	Y	-	286 (285.8)	R	-1200 +900	-	-	RNP APCH

2. HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/ Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PQ501	Y	286 (285.8)	+0.4	1 ≤ FL140 1.5 > FL140	R	-1200 +900	-430 ≤ FL140 -445 > FL140	RNP APCH