

APCH procedure coding of ILS Y RWY 10

1. ILS Y RWY 10: INITIAL APPROACH SEGMENT FROM PQ501

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	PQ501	-	-	-		900			RNP 1
TF	PQ210	-	54.2	286 (285.8)	-	-	-	-	RNP 1
TF	PQ110	-	13.0	006 (005.7)	R	800	-	-	RNP 1

2. ILS Y RWY 10: MISSED APPROACH SEGMENT

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	MAPT	Y	-	-	-	-	-	-	RNP 1
DF	PQ500	Y	-	-	-	-	-	-	RNP 1
TF	PQ501	-	33.5	138 (137.6)	R	900	-	-	RNP 1
HM	PQ501	Y	-	286 (285.8)	R	-1200 +900	-	-	RNP 1

3. HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/ Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PQ501	Y	286 (285.8)	+0.4	1 ≤ FL140	R	-1200 +900	-430 ≤ FL140	RNP 1