

APCH procedure coding of ILS Y RWY 28**1. ILS Y RWY 28: INITIAL APPROACH SEGMENT FROM PQ601**

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	PQ601	-	-	-	-	900	-	-	RNP 1
TF	PQ428	-	45.3	077 (076.1)	-	-	-	-	RNP 1
TF	PQ128	-	13.0	006 (005.7)	L	800	-	-	RNP 1

2. ILS Y RWY 28: MISSED APPROACH SEGMENT

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	MAPT	Y	-	-	-	-	-	-	RNP 1
DF	PQ600	Y	-	-	-	-	-	-	RNP 1
TF	PQ601	-	33.6	219 (218.8)	L	900	-	-	RNP 1
HM	PQ601	Y	-	077 (076.1)	R	-1200 +900	-	-	RNP 1

3. HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/ Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PQ601	Y	077 (076.1)	+0.4	1 ≤ FL140	R	-1200 +900	-430 ≤ FL140	RNP 1