

APCH procedure coding of ILS X RWY 28

1. ILS X RWY 28: INITIAL APPROACH SEGMENT FROM PQ601

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	PQ601	-	-	-	-	900	-	-	RNP 1
TF	PQ528	-	51.0	042 (041.9)	-	-	-	-	RNP 1
TF	PQ328	-	12.5	096 (095.7)	R	-	-	-	RNP 1
TF	PQ128	-	13.0	186 (185.7)	R	800	-	-	RNP 1

2. ILS X RWY 28: MISSED APPROACH SEGMENT

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	MAPT	Y	-	-	-	-	-	-	RNP 1
DF	PQ600	Y	-	-	-	-	-	-	RNP 1
TF	PQ601	-	33.6	219 (218.8)	L	900	-	-	RNP 1
HM	PQ601	Y	-	077 (076.1)	R	-1200 +900	-	-	RNP 1

3. HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/ Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PQ601	Y	077 (076.1)	+0.4	1 ≤ FL140	R	-1200 +900	-430 ≤ FL140	RNP 1