

AD OPERATING MINIMA

ILS approach procedure for RWY 28	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	110	900	1 100
	C, D	115	1 000	1 100

ILS approach procedure for RWY 28 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	205		1 600
	C	205		2 800
	D	205		3 200

ILS Z, ILS Y, ILS X approach procedure for RWY 28	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	110	900	1 100
	C, D	115	1 000	1 100

ILS Z, ILS Y, ILS X approach procedure for RWY 28 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	205		1 600
	C	205		2 800
	D	205		3 200

3. RNP approach procedure

RNP (LNAV) Z, Y, X approach procedure for RWY 10	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	220		2 000
	C	220		3 600
	D	220		4 000

RNP (LNAV) Z, Y, X approach procedure for RWY 28	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	315		4 600