

APCH procedure and TRANSITION coding of RNP RWY 07R**1. RNP RWY CHC 07R: APPROACH FROM SAMDU**

Rcmd.Path Terminator	Fix ID (Wpt Name)	Fly-Over	Distance (KM)	Track		Turn Direction	Altitude (M)	Speed Limit (IAS) KH/H	Ver Angle	Nav Spec
				Mag Track	True Track					
IF	SAMDU	-	-	-	-	-	-1500	-425	-	RNP APCH
TF	TS516	-	9.2	028	026.9	-	+600	-	-	RNP APCH
TF	TS514	-	6.9	070	069.1	-	@600	-	-	RNP APCH
TF	RW07R	Y	11.2	070	069.1	-	-	-	-3°	RNP APCH
CF	TS592	-	16.5	070		-	-	-	-	RNP APCH
TF	TS596	-	13.0	160	159.1	-	-	-	-	RNP APCH
TF	TUNBI	-	25.6	190	188.8	-	@900	-425	-	RNP APCH
HM	TUNBI	-	-	001	360.0	L	@900	-405	-	RNP APCH

2. RNAV HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)		Magnetic Variation	Time (s)	Turn Direction	Altitude (M)	Speed (KM/H)	Nav Spec
TUNBI	Y	001	360.0	+1	60	L	@900	-405	RNAV 1