

Procedure coding

1. ILS X RWY 07R

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (km)	TRACK		TURN DIRECTION	ALTITUDE (m)	SPEED LIMIT (IAS) km/h	VER ANGLE	NAV SPEC
				MAG TRACK	TRUE TRACK					
IF	SAMDU	-	-	-		-	-1500	-425	-	RNAV 1
TF	TS516	-	9.2	028	026.9	-	+600	-	-	RNAV 1
TF	TS512	-	7.1	070	069.1	-	@600	-	-	RNAV 1
TF	RW07R	Y	11.0	070	069.1	-	-	-	-3.0°	X
CF	TS592	-	16.5	070		-	-	-	-	RNAV 1
TF	TS596	-	13.0	160	159.1	-	-	-	-	RNAV 1
TF	TUNBI	-	25.6	190	188.8	-	@900	-425	-	RNAV 1
HM	TUNBI	-	-	001	360.0	L	@900	-405	-	RNAV 1

2. RNAV HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)		Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
TUNBI	-	001	360.0	+1	60	L	@900	-405	RNAV 1