

AD OPERATING MINIMA

TAN SON NHAT WEATHER MNM
VVTS

2. VOR approach procedures

VOR approach procedure for RWY 25L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	155		2 000
	D	155		2 800

VOR approach procedure for RWY 25R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility(M)
	A, B, C, D	145		2 800

VOR approach procedure for RWY 07L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	145		2 000
	C, D	145		2 300

VOR approach procedure for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	145		2 000
	C, D	145		2 300

3. NDB approach procedures

NDB approach procedure for RWY 25L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	120		1 600
	D	120		2 000

NDB approach procedure for RWY 25R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	165		2 600
	D	165		2 800

NDB approach procedure for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	163		1 600
	C, D	163		2 000

Circling for RWY 07R/L and 25L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	190		2 400
	C	290		4 400
	D	290		4 800