

**Procedure coding****1. RNAV RWY 25L: ANTRI ONE CHARLIE DEPARTURE (ANTRI 1C)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	250 (249.0)	1° W	12.0	-	-	-	-	RNAV1
2	TF	TS017	-	172 (171.0)	1° W	28.7	L	-3050	-	-	RNAV1
3	TF	TS018	-	082 (081.0)	1° W	22.0	L	+3650	-	-	RNAV1
4	TF	TS019	-	051 (050.0)	1° W	32.0	L	-	-	-	RNAV1
5	TF	ANTRI	-	030 (028.7)	1° W	54.0	L	-	-	-	RNAV1

**PATMA TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ANTRI	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	PATMA	-	027 (025.6)	1° W	144.2	-	+FL290	-	-	RNAV1

**2. RNAV RWY 25L: BACHU ONE FOXTROT DEPARTURE (BACHU 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	250 (249.0)	1° W	12.0	-	-	-	-	RNAV1
2	TF	TS020	-	250 (249.0)	1° W	26.5	-	-3350 +1250	-	-	RNAV1
3	TF	BACHU	-	252 (251.1)	1° W	34.9	R	-	-	-	RNAV1

**3. RNAV RWY 25L: KADUM ONE FOXTROT DEPARTURE (KADUM 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	250 (249.0)	1° W	12.0	-	-	-410	-	RNAV1
2	TF	TS016	-	340 (339.0)	1° W	16.7	R	-	-	-	RNAV1
3	TF	KADUM	-	053 (052.1)	1° W	80.1	R	-	-	-	RNAV1

**PATMA TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	KADUM	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	PATMA	-	038 (037.0)	1° W	136.0	-	+FL290	-	-	RNAV1

**4. RNAV RWY 25L: ENPAS ONE FOXTROT DEPARTURE (ENPAS 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	250 (249.0)	1° W	12.0	-	-	-	-	RNAV1
2	TF	TS020	-	250 (249.0)	1° W	26.5	-	-3350 +1250	-	-	RNAV1
3	TF	ENPAS	-	215 (214.3)	1° W	38.4	L	-	-	-	RNAV1

**ANHOA TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ENPAS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	ANHOA	-	199 (198.2)	1° W	71.3	-	+FL200	-	-	RNAV1