

Procedure coding (cont.)**3. RWY 25L/R - RNAV 1: ENPAS TWO DELTA DEPARTURE (ENPAS 2D)****INITIAL CLIMB RWY 25L**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1

INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1

ENPAS 2D CODING FROM TS616

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
3	TF	ENPAS	-	215 (214.3)	+1	38.4	-	-	-	RNAV 1

ANHOA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ENPAS	-	-	+1	-	-	-	-	RNAV 1
2	TF	ANHOA	-	199 (198.2)	+1	71.3	-	-	-	RNAV 1

4. RWY 25L/R - RNAV 1: XOBAV TWO DELTA DEPARTURE (XOBAV 2D)**INITIAL CLIMB RWY 25L**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1

INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1

XOBAV 2D CODING FROM TS616

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS641	-	172 (171.2)	+1	27.8	-	-2750	-	RNAV 1
3	TF	TS642	-	172 (171.2)	+1	13.0	-	-3350	-	RNAV 1
4	TF	TS644	-	172 (171.3)	+1	21.9	-	-4250	-	RNAV 1
5	TF	XOBAV	-	165 (164.4)	+1	8.3	-	-	-	RNAV 1

NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	XOBAV	-	-	+1	-	-	-	-	RNAV 1
2	TF	NIXIV	-	182 (180.7)	+1	82.6	-	-	-	RNAV 1

5. RWY 25L/R - RNAV 1: MISAN TWO DELTA DEPARTURE (MISAN 2D)**INITIAL CLIMB RWY 25L**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1

INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1

MISAN 2D CODING FROM TS616

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
3	TF	MISAN	-	232 (231.2)	+1	36.3	-	-	-	RNAV 1