

**Procedure coding (cont.)****3. RNAV RWY 07L: XOBAY ONE FOXTROT ARRIVAL (XOBAY 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	XOBAY	-	-	1° W	-	-	-4250	-	-	RNAV1
2	TF	TS029	-	351 (349.7)	1° W	44.4	-	-	-	-	RNAV1
3	TF	TS026	-	340 (339.0)	1° W	13.0	L	-3050	-410	-	RNAV1
4	TF	TS025	-	250 (249.0)	1° W	29.6	L	-	-410	-	RNAV1
5	TF	TS024	-	340 (339.0)	1° W	13.0	R	-	-370	-	RNAV1
6	TF	TS023	-	070 (069.0)	1° W	7.4	R	-	-370	-	RNAV1
7	TF	TS022	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	TS021	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	BUNVI	-	062 (061.1)	1° W	8.4	L	+600	-370	-	RNAV1

**ELSAS TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ELSAS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS033	-	271 (270.2)	1° W	74.3	-	-FL150	-	-	RNAV1
3	TF	XOBAY	-	272 (270.5)	1° W	25.0	-	-4250	-	-	RNAV1

**4. RNAV STAR RWY 07L: SAPEN TWO KILO ARRIVAL (SAPEN 2K)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	SAPEN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS032	-	114 (113.3)	1° W	23.4	-	-3050	-410	-	RNAV1
3	TF	TS031	-	181 (180.0)	1° W	10.7	R	-	-410	-	RNAV1
4	TF	TS030	-	250 (249.0)	1° W	14.8	R	-	-410	-	RNAV1
5	TF	TS023	-	160 (159.0)	1° W	13.0	L	-	-370	-	RNAV1
6	TF	TS022	-	070 (069.0)	1° W	7.4	L	-	-370	-	RNAV1
7	TF	TS021	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	BUNVI	-	062 (061.1)	1° W	8.4	L	+600	-370	-	RNAV1

**5. RNAV RWY 07R: BAOMY TWO ECHO ARRIVAL (BAOMY 2E)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	BAOMY	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS028	-	254 (252.9)	1° W	41.6	-	+3950	-	-	RNAV1
3	TF	TS027	-	256 (255.0)	1° W	22.2	R	+3350	-	-	RNAV1
4	TF	TS026	-	256 (255.0)	1° W	27.4	-	-3050	-410	-	RNAV1
5	TF	TS025	-	250 (249.0)	1° W	29.6	L	-	-410	-	RNAV1
6	TF	TS024	-	340 (339.0)	1° W	13.0	R	-	-370	-	RNAV1
7	TF	TS023	-	070 (069.0)	1° W	7.4	R	-	-370	-	RNAV1
8	TF	TS022	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	TS021	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	VEXID	-	070 (068.8)	1° W	8.3	-	+600	-370	-	RNAV1

**MEKIN TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	MEKIN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BAOMY	-	206 (204.9)	1° W	53.2	-	-	-	-	RNAV1