

Procedure coding (cont.)**8. RNAV RWY 07R: SAPEN TWO LIMA ARRIVAL (SAPEN 2L)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	SAPEN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS032	-	114 (113.3)	1° W	23.4	-	-3050	-410	-	RNAV1
3	TF	TS031	-	181 (180.0)	1° W	10.7	R	-	-410	-	RNAV1
4	TF	TS030	-	250 (249.0)	1° W	14.8	R	-	-410	-	RNAV1
5	TF	TS023	-	160 (159.0)	1° W	13.0	L	-	-370	-	RNAV1
6	TF	TS022	-	070 (069.0)	1° W	7.4	L	-	-370	-	RNAV1
7	TF	TS021	-	070 (069.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	VEKID	-	070 (068.8)	1° W	8.3	-	+600	-370	-	RNAV1

9. RNAV HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
BAOMY	Y	251 (250.0)	1° W	1 ≤ 4250 1.5 > 4250	L	+3950	-430 ≤ 4250 -450 > 4250	RNAV1
MEKIN	Y	223 (222.0)	1° W	1 = 4250 1.5 > 4250	L	+4250	-430 = 4250 -450 > 4250	RNAV1
VETOM	Y	236 (235.0)	1° W	1 = 4250 1.5 > 4250	L	+4250	-430 = 4250 -450 > 4250	RNAV1
PTH	Y	266 (265.0)	1° W	1 = 4250 1.5 > 4250	R	+4250	-430 = 4250 -450 > 4250	RNAV1
BITIS	Y	039 (038.0)	1° W	1 ≤ 4250 1.5 > 4250	R	+3650	-430 ≤ 4250 -450 > 4250	RNAV1
SAPEN	Y	115 (114.0)	1° W	1 ≤ 4250 1.5 > 4250	R	+3650	-430 ≤ 4250 -450 > 4250	RNAV1
XOBAV	Y	001 (360.0)	1° W	1 ≤ 4250 1.5 > 4250	L	+2150	-430 ≤ 4250 -450 > 4250	RNAV1

10. CONVENTIONAL HOLDING PROCEDURE

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)
ELSAS	309 (308.0)	1° W	1 = 4250 1.5 > 4250	L	+4250	-430 = 4250 -450 > 4250