

Procedure coding**1. RNAV RWY 25L: BAOMY TWO FOXTROT ARRIVAL (BAOMY 2F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	BAOMY	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS008	-	251 (249.9)	1° W	30.4	-	-3050 +1200	-410	-	RNAV1
3	TF	TS007	-	160 (159.0)	1° W	28.3	L	-	-410	-	RNAV1
4	TF	TS006	-	250 (249.0)	1° W	13.0	R	-	-370	-	RNAV1
5	TF	TS005	-	340 (339.0)	1° W	7.4	R	-	-370	-	RNAV1
6	TF	TS004	-	340 (339.0)	1° W	7.4	-	+900	-370	-	RNAV1
7	TF	TS003	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	TS002	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	TS001	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	SOKAN	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
11	TF	XIMLA	-	275 (273.8)	1° W	10.5	L	+750	-370	-	RNAV1

MEKIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	MEKIN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BAOMY	-	206 (204.9)	1° W	53.2	-	-	-	-	RNAV1

VETOM TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VETOM	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BAOMY	-	218 (217.2)	1° W	50.3	-	-	-	-	RNAV1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	PTH	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BAOMY	-	266 (265.0)	1° W	81.5	-	-	-	-	RNAV1

ELSAS TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ELSAS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BAOMY	-	345 (343.6)	1° W	84.7	-	-	-	-	RNAV1

2. RNAV RWY 25L: BITIS TWO FOXTROT ARRIVAL (BITIS 2F)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	BITIS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS012	-	038 (037.4)	1° W	49.7	-	+3650	-	-	RNAV1
3	TF	TS011	-	070 (069.0)	1° W	17.4	R	+3350	-	-	RNAV1
4	TF	TS010	-	070 (069.0)	1° W	18.3	-	-3050	-410	-	RNAV1
5	TF	TS009	-	160 (159.0)	1° W	26.5	R	-	-410	-	RNAV1
6	TF	TS005	-	070 (069.0)	1° W	13.0	L	-	-370	-	RNAV1
7	TF	TS004	-	340 (339.0)	1° W	7.4	L	+900	-370	-	RNAV1
8	TF	TS003	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	TS002	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	TS001	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
11	TF	SOKAN	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
12	TF	XIMLA	-	275 (273.8)	1° W	10.5	L	+750	-370	-	RNAV1