

Procedure coding

1. RWY 07L/R - RNAV 1: BITIS TWO GOLF ARRIVAL (BITIS 2G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	BITIS	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS566	-	029 (028.3)	+1	23.3	-	@1500	-460	RNAV 1
3	TF	TS564	-	097 (096.3)	+1	16.7	-	-	-	RNAV 1
4	TF	TS562	-	062 (061.3)	+1	16.7	-	@1500	-	RNAV 1
5	TF	SAMDU	-	315 (313.8)	+1	27.8	-	-1500	-425	RNAV 1

TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TRN	-	-	+1	-	-	-	-	RNAV 1
2	TF	BITIS	-	072 (071.2)	+1	62.8	-	-	-	RNAV 1

2. RWY 07L/R - RNAV 1: SAPEN TWO GOLF ARRIVAL (SAPEN 2G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	SAPEN	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS584	-	114 (113.3)	+1	15.6	-	-	-	RNAV 1
3	TF	TS582	-	204 (203.4)	+1	16.2	-	-2450	-	RNAV 1
4	TF	LOTVU	-	204 (203.3)	+1	15.9	-	@1500	-460	RNAV 1
5	TF	TS568	-	167 (166.3)	+1	16.7	-	-	-	RNAV 1
6	TF	TS566	-	132 (131.3)	+1	16.7	-	-	-	RNAV 1
7	TF	TS564	-	097 (096.3)	+1	16.7	-	-	-	RNAV 1
8	TF	TS562	-	062 (061.3)	+1	16.7	-	@1500	-	RNAV 1
9	TF	SAMDU	-	315 (313.8)	+1	27.8	-	-1500	-425	RNAV 1

3. RNAV HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
BITIS	Y	029 (028.0)	+1	90	L	- FL200 +2450	-425	RNAV 1