

**Procedure coding****1. RWY 07L/R - RNAV 1: DALAP TWO GOLF ARRIVAL (DALAP 2G)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	DALAP	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS548	-	219 (218.1)	+1	34.1	-	-	-	RNAV 1
3	TF	TS546	-	263 (262.3)	+1	43.5	-	+3350	-460	RNAV 1
4	TF	TS544	-	229 (228.0)	+1	5.6	-	+3050	-	RNAV 1
5	TF	ENROP	-	229 (227.9)	+1	17.9	-	@2150	-	RNAV 1
6	TF	TS542	-	217 (216.3)	+1	6.3	-	-	-	RNAV 1
7	TF	TS538	-	242 (241.3)	+1	14.5	-	-	-	RNAV 1
8	TF	TS536	-	277 (276.3)	+1	14.5	-	-	-	RNAV 1
9	TF	TS534	-	312 (311.3)	+1	14.5	-	@2150	-	RNAV 1
10	TF	SAMDU	-	060 (058.8)	+1	24.1	-	-1500	-425	RNAV 1

**RINKU TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS918	-	135 (134.2)	+1	26.5	-	-	-	RNAV 1
3	TF	TS916	-	147 (146.2)	+1	26.5	-	-	-	RNAV 1
4	TF	TS914	-	159 (158.3)	+1	26.5	-	-	-	RNAV 1
5	TF	TS912	-	171 (170.3)	+1	26.5	-	-	-	RNAV 1
6	TF	RINKU	-	183 (181.9)	+1	24.7	-	-	-	RNAV 1
7	TF	DALAP	-	278 (277.4)	+1	127.0	-	-	-	RNAV 1

**DOVIN TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
2	TF	DALAP	-	219 218.2	+1	127.0	-	-	-	RNAV 1

**VETOM TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VETOM	-	-	+1	-	-	-	-	RNAV 1
2	TF	DALAP	-	226 (224.6)	+1	34.0	-	-	-	RNAV 1

**PTH TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	PTH	-	-	+1	-	-	-	-	RNAV 1
2	TF	DALAP	-	278 (277.3)	+1	75.2	-	-	-	RNAV 1

**2. RWY 07L/R - RNAV 1: VICAL THREE GOLF ARRIVAL (VICAL 3G)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VICAL	-	-	+1	-	-	-3650	-	RNAV 1
2	TF	TS538	-	323 (321.7)	+1	45.3	-	@2150	-460	RNAV 1
3	TF	TS536	-	277 (276.3)	+1	14.5	-	-	-	RNAV 1
4	TF	TS534	-	312 (311.3)	+1	14.5	-	@2150	-	RNAV 1
5	TF	SAMDU	-	060 (058.8)	+1	24.1	-	-1500	-425	RNAV 1

**NIXIV TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NIXIV	-	-	+1	-	-	-	-	RNAV 1
2	TF	VICAL	-	010 (008.7)	+1	84.3	-	-3650	-	RNAV 1

**ELSAS TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ELSAS	-	-	+1	-	-	-	-	RNAV 1
2	TF	VICAL	-	272 (270.8)	+1	87.4	-	-3650	-	RNAV 1