

**APCH procedure coding of RNP Y RWY 03****1. RNP APPROACH PROCEDURE RWY 03 FROM VD901**

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	VD901	-	-	-	-	+900	-	-	RNP APCH
TF	VD902	-	16.7	269°(267.1°)	-	-	-	-	RNP APCH
TF	VD031	-	9.3	298°(295.8°)	R	800	-	-	RNP APCH
TF	VD030	-	9.9	028°(025.8°)	R	540	-	-	RNP APCH
TF	THR03	Y	9.9	028°(025.9°)	-	255	-	-5.2%	RNP APCH
DF	VD900	Y	-	-	R	-	-	-	RNP APCH
DF	VD901	-	-	-	R	900	-	-	RNP APCH
HM	VD901	-	-	-	L	+900	-	-	RNP APCH

**2. RNP HOLDING PROCEDURE**

HOLDING FIX	FLY- OVER	INBOUND COURSE/TRACK °M(°T)	MAGNETIC VARIATION	TIME (MIN)	TURN DIRECTION	ALTITUDE (M)	SPEED (KM/H)	NAV SPEC
VD901	Y	230°(228.2°)	+1.8	1 ≤ FL140 1.5 > FL140	L	+900	-430 ≤ FL140 -445 > FL140	RNP APCH